



21600 NORDHOFF ST.
CHATSWORTH, CALIFORNIA 91311 USA
PH: (818) 882-1238, E-Mail: sor@sor.com
Internet: <http://www.sor.com>

#309-4700 TUFF DUCK SLIP COVER

FITS 1/79-1984 FJ45/HJ47 PICK UP LEFT HAND DRIVE

PLEASE READ INSTRUCTIONS BEFORE INSTALLATION

Warm up slip covers in the sun till they are soft and warm before installation. Or you can put slip cover inside pillow case and put in clothes dryer for a few minutes. Be careful to close the pillow case so the slip covers do not come in contact with the dryer drum, other wise you will melt the backing on this slip cover.

Be sure the hook and loop strips sewn on the bottom of the cushion on each side are separated. The tags on the back of the seat pockets should be facing each other.

INSTALLATION PROCEDURES

- STEP 1.** Snugly fit the passenger side cover over the backrest and cushion.
- STEP 2.** Fit the center flap with two hook and loop strips sewn on into the opening between the top of the cushion and bottom of the backrest. Be sure the center flap goes through to the back.
- STEP 3.** Stretch the bottom side pieces back and mate the hook and loop strips with the hook and loop strips sewn on the center flap.
- STEP 4.** Be sure the cover is positioned behind the backrest release lever.
- STEP 5.** Repeat STEPS 1 through 4 to install the driver side seat cover.

CARE INSTRUCTIONS

Cold water wash, line dry. May be dry cleaned, no trichlorethylene.

NOTE: if covers are left in direct sunlight for extended periods of time covers will tend to fade.