



21600 NORDHOFF ST.
CHATSWORTH, CALIFORNIA 91311 USA
PH: (818) 882-1238, E-Mail: sor@sor.com
Internet: <http://www.sor.com>

#309-5502-T FRONT TUFF DUCK SLIP COVER

FITS 9/75-7/80 FJ55

PLEASE READ INSTRUCTIONS BEFORE INSTALLATION

Warm up slip covers in the sun till they are soft and warm before installation. Or you can put slip cover inside pillow case and put in clothes dryer for a few minutes. Be careful to close the pillow case so the slip covers do not come in contact with the dryer drum, other wise you will melt the backing on this slip cover.

Be sure the hook and loop strips sewn on the underside of each cover are separated.

INSTALLATION INSTRUCTIONS

- STEP 1.** Position the cover over the backrest, slipping the two long straps into the opening between the bottom of the backrest and top of the cushion. **MAKE SURE** the straps go through to the back.
- STEP 2.** Fit the seat belt through the openings in the cover and position the cover over the cushion.
- STEP 3.** On each side, pull the flap around the seat and securely mate the hook and loop strip on the flap with the hook and loop strip on the **UNDERSIDE** of the backrest cover.
- STEP 4.** Pull the two long straps **UNDER** the cushion and securely mate to the corresponding hook and loop strips sewn on the front, bottom underside of the cushion.

After a few days of normal use, the covers will conform to the contour of your seats.

CARE INSTRUCTIONS

Cold water wash, line dry. May be dry cleaned, no trichlorethylene.

NOTE: if covers are left in direct sunlight for extended periods of time covers will tend to fade.