



21600 NORDHOFF ST.  
CHATSWORTH, CALIFORNIA 91311 USA  
PH: (818) 882-1238 E-Mail: sor@sor.com  
Internet: <http://www.sor.com>

---

## #309-701-R REAR BENCH SEATS TUFF DUCK SLIP COVER FITS 1984-1989 BJ70

### **PLEASE READ INSTRUCTIONS BEFORE INSTALLATION**

Warm up slip covers in the sun till they are soft and warm before installation. Or you can put slip cover inside pillow case and put in clothes dryer for a few minutes. Be careful to close slip cover so the slip covers do not come in contact with the dryer drum, other wise you will melt the backing on this slip cover.

Be sure the hook and loop strips sewn on the underside of the headrest covers, and along the back and sides of the cushions are separated. When properly installed, the tags on the back seat pockets should be facing each other.

### **INSTALLATION PROCEDURES**

STEP 1. Remove the headrest.

STEP 2. Tilt the cushion forward by pulling upward on the center release strap. Unlatch the backrest and tilt forward slightly.

STEP 3. Center the cover over the backrest, making sure the cutouts for the side latches and top brackets align properly.

STEP 4. Stretch the elastic around each top and bottom corner. Return the backrest to the latches position.

STEP 5. Align the cover over the cushion, making sure the center strap fits through the elastic cutout. Return the cushion to the sitting position.

STEP 6. Reinstall the headrests and secure in the upper, first latch position.

STEP 7. Fit a cover over each headrest. Mate the hook and loop strips on the underside.

After a few days of normal use, the covers will conform to the contour of your seats.

### **CARE INSTRUCTIONS**

Cold water wash, line dry. May be dry cleaned, no trichlorethylene.

NOTE: if covers are left in direct sunlight for extended periods of time covers will tend to fade.