



21600 NORDHOFF ST.
CHATSWORTH, CALIFORNIA 91311 USA
PH: (818) 882-1238, E-Mail: sor@sor.com
Internet: <http://www.sor.com>

#309-7010-F

BJ70 FRONT TUFF DUCK SLIP COVERS

FITS 11/84-1/90 BJ70

PLEASE READ INSTRUCTIONS BEFORE INSTALLATION

Warm up slip covers in the sun till they are soft and warm before installation. Or you can put slip cover inside pillow case and put in clothes dryer for a few minutes. Be careful to close the pillow case so the slip covers do not come in contact with the dryer drum, other wise you will melt the backing on this slip cover.

INSTALLATION INSTRUCTIONS

- STEP 1.** Remove the headrests from the seat back.
- STEP 2.** Position the cover over the front seat back rest, connect the flap on the bottom of the slip cover to securely mate the front to back for a nice tight fit. Be sure the holes for the headrest are properly aligned at the top of the seat back. When properly installed the pit bull tested tags on the back seat pockets will be side by side in the center of the back seat.
- STEP 3.** Position the slipcover over the bottom seat cushion. Pull the bottom sides around the bottom of the cushion and securely mate them with the hook and loop on the back side of the slip cover for a nice tight fit.
- STEP 4.** Fit the new headrest covers over the headrests and reinstall.

After a few days of normal use, the covers will conform to the contour of your seats.

CARE INSTRUCTIONS

Cold water wash, line dry. May be dry cleaned, no Trichlorethylene.

NOTE: if covers are left in direct sunlight for extended periods of time covers will tend to fade.